DOMUS LINE

FLEXYLED UHE6 PW

Domus Line
design

Flexible pre-wired sliding LED modules

Materials:
flexible LED strip without adhesive
Covering:
high reflectance paint
Light source:
static light LED module
Number of LEDs:
280 LED/metre
Application type:
universal
Installation:
slide inside small profiles

FLEXYLED UHE6 PW is an LED strip with **280 LED/m on a circuit of only 6 mm wide**. Developed to be integrated **"sliding" within small profiles** (e.g. APEX), it is supplied in modules of 100 cm, 200 cm, 250 cm and 300 cm with power supply and connector (pre-wired). These modules are designed with **reinforced soldered power supply cable terminals** which ensure good solidity.

	Colour appearance	natural white
	Colour temperature	4000 K
	Luminous efficiency	82 lm/W
	CRI	Ra ≥ 80

	Colour appearance	warm white
	Colour temperature	3000 K
	Luminous efficiency	82 lm/W
	CRI	Ra ≥ 80

	Colour appearance	super warm white
	Colour temperature	2700 K
	Luminous efficiency	82 lm/W
	CRI	Ra ≥ 80

* values referring to FLEXYLED UHE6 PW 1000 mm

TECHNICAL DATA

Power	10W/m
Power supply	24Vdc
LEDs/metre	280
Divisibility	2.5 cm (7 LED)
Cable	2000 mm
Protection	IP20
Adhesive 3M©	no

Compatible with:

APEX
APEX H7
MISS*
LAB*

A PRODUCT AVAILABLE. VALIDATED TECHNICAL AND PHOTOMETRIC DATA.

* can integrate APEX profile

FLEXYLED UHE6 PW
modules with 280 LED/metre

Code	Length	Watt & Volt	LED
1349301_*/UHE	1000mm	10W @ 24Vdc	280
1349401_*/UHE	2000mm	20W @ 24Vdc	560
1349501_*/UHE	2500mm	25W @ 24Vdc	700
1349601_*/UHE	3000mm	30W @ 24Vdc	840

Code	Light colour*
N	natural white
B	warm white
B1	super warm white

LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.

24Vdc

Micro 24

[1] For UL-certified model codes, see the **American standard LED collection catalogue**, also available at www.domusline.com

For power supplies and accessories see page 38 or browse the Domus Extra catalogue.